

NORMALIZED FELTS FOR VESLIC

FELTRINI NORMALIZZATI PER VESLIC

NORMALIZED FELTS FOR RUB FASTNESS TESTER VESLIC

Normalized, White or Black, Wool Felts, used to **test the resistance of the color to dry and wet rubbing** with Veslic (Rub Fastness Tester).

According to:

- ISO 11640
- IUF 450
- VESLIC C-4500

Technical Specifications of Felts for Veslic:

- Dimensions: 15 mm x 15 mm
- Thickness: 6.0 mm +/- 0.5 mm
- Material: pure wool felt
- Weight: 1900 g/m² +/-150 g/m²
- Density: 0.32 g/cm³ -0.37 g/cm³
- pH: 4.0 – 8.0

Each package contains 1000pcs



FELTRINI NORMALIZZATI PER VESLIC

Feltrini Normalizzati, Bianchi o Neri, usati per **testare la resistenza del colore allo sfregamento a secco e a umido** con apparecchio Veslic.

Conformi alle norme:

- ISO 11640
- IUF 450
- VESLIC C-4500

I feltrini per Veslic hanno le seguenti caratteristiche

- Dimensione: 15 mm x 15 mm
- Spessore: 6.0 mm +/- 0.5 mm
- Materiale: feltro in pura lana
- Peso: 1900 g/m² +/-150 g/m²
- Densità: 0.32 g/cm³ -0.37 g/cm³
- pH: 4.0 – 8.0

Ogni confezione contiene 1000 feltrini.

